



UT8205AZ

Preliminary

Power MOSFET

N-CHANNEL ENHANCEMENT MODE



DESCRIPTION

The **UT8205AZ** uses advanced technology to provide fast switching, low on-resistance and cost-effectiveness. This device is suitable for all commercial-industrial surface mount applications.

FEATURES

- * $R_{DS(ON)} \leq 28 \text{ m}\Omega$ @ $V_{GS}=4.5\text{V}$, $I_D=6.0\text{A}$
- * Ultra low gate charge (typical 23 nC)
- * Low reverse transfer Capacitance (C_{RSS} = typical 150 pF)
- * Fast switching capability
- * Avalanche energy Specified
- * Improved dv/dt capability, high ruggedness

SYMBOL



ORDERING INFORMATION

| Ordering Number | Package | Pin Assignment | | | | | | | | Packing |
|-----------------|---------|----------------|----|----|----|----|----|----|---|-----------|
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | |
| UT8205AZG-AG6-R | SOT-26 | S1 | D | S2 | G2 | D | G1 | - | - | Tape Reel |
| UT8205AZG-S08-R | SOP-8 | D | S1 | S1 | G1 | G2 | S2 | S2 | D | Tape Reel |
| UT8205AZG-P08-R | TSSOP-8 | D | S1 | S1 | G1 | G2 | S2 | S2 | D | Tape Reel |

Note: Pin Assignment: S: Source G: Gate D: Drain

| | |
|---|---|
| <p>UT8205AZG-AG6-R</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p> | <p>(1) R: Tape Reel</p> <p>(2) AG6: SOT-26, P08: TSSOP-8, S08: SOP-8</p> <p>(3) G: Halogen Free and Lead Free</p> |
|---|---|

MARKING

| SOP-8 | TSSOP-8 | SOT-26 |
|-------|---------|--------|
| | | |

■ ABSOLUTE MAXIMUM RATINGS

| PARAMETER | | SYMBOL | RATINGS | UNIT |
|---|------------|-----------|------------|------------------|
| Drain-Source Voltage | | V_{DSS} | 20 | V |
| Gate-Source Voltage | | V_{GSS} | ± 12 | V |
| Drain Current (Note 2) | Continuous | I_D | 6 | A |
| | Pulsed | I_{DM} | 20 | A |
| Power Dissipation ($T_A=25^\circ\text{C}$) (Note 3) | SOT-26 | P_D | 1.14 | W |
| | SOP-8 | | 1.6 | W |
| | TSSOP-8 | | 1 | W |
| Junction Temperature | | T_J | +150 | $^\circ\text{C}$ |
| Storage Temperature | | T_{STG} | -55 ~ +150 | $^\circ\text{C}$ |

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Pulse Test : Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$

3. Pulse width limited by $T_{J(MAX)}$

■ THERMAL DATA

| PARAMETER | | SYMBOL | RATINGS | UNIT |
|----------------------------|---------|---------------|---------|--------------------|
| Junction to Ambient (Note) | SOT-26 | θ_{JA} | 110 | $^\circ\text{C/W}$ |
| | SOP-8 | | 78 | $^\circ\text{C/W}$ |
| | TSSOP-8 | | 125 | $^\circ\text{C/W}$ |

Note: Pulse Test : Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$

■ ELECTRICAL CHARACTERISTICS ($T_J=25^\circ\text{C}$, unless otherwise specified)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|--------------------------------------|--|-----|------|----------|---------------------------|
| OFF CHARACTERISTICS | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_D=250\mu\text{A}$ | 20 | | | V |
| Breakdown Voltage Temperature Coefficient | $\frac{\Delta BV_{DSS}}{\Delta T_J}$ | $I_D=1\text{mA}$, Reference to 25°C | | 0.03 | | $\text{V}/^\circ\text{C}$ |
| Drain-Source Leakage Current | I_{DSS} | $V_{DS}=20V, V_{GS}=0V,$ | | | 1 | μA |
| Gate-Source Leakage Current | I_{GSS} | $V_{GS}=\pm 8V$ | | | ± 10 | μA |
| ON CHARACTERISTICS | | | | | | |
| Gate Threshold Voltage | $V_{GS(TH)}$ | $V_{DS}=V_{GS}, I_D=250\mu\text{A}$ | 0.5 | | 1.5 | V |
| Drain-Source On-State Resistance (Note) | $R_{DS(ON)}$ | $V_{GS}=4.5V, I_D=6.0A$ | | | 28 | $\text{m}\Omega$ |
| | | $V_{GS}=2.5V, I_D=5.2A$ | | | 38 | $\text{m}\Omega$ |
| DYNAMIC PARAMETERS | | | | | | |
| Input Capacitance | C_{ISS} | $V_{DS}=20V, V_{GS}=0V, f=1.0\text{MHz}$ | | 1035 | | pF |
| Output Capacitance | C_{OSS} | | | 320 | | pF |
| Reverse Transfer Capacitance | C_{RSS} | | | 150 | | pF |
| SWITCHING PARAMETERS | | | | | | |
| Turn-ON Delay Time (Note) | $t_{D(ON)}$ | $V_{GS}=5V, V_{DS}=10V, R_D=10\Omega, R_G=6\Omega, I_D=1A$ | | 30 | | ns |
| Turn-ON Rise Time | t_R | | | 70 | | ns |
| Turn-OFF Delay Time | $t_{D(OFF)}$ | | | 40 | | ns |
| Turn-OFF Fall-Time | t_F | | | 65 | | ns |
| Total Gate Charge(Note) | Q_G | | | 23 | | nC |
| Gate Source Charge | Q_{GS} | $V_{DS}=20V, V_{GS}=5V, I_D=6.0A$ | | 4.5 | | nC |
| Gate Drain Charge | Q_{GD} | | | 7 | | nC |
| SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS | | | | | | |
| Drain-Source Diode Forward Voltage (Note) | V_{SD} | $I_S=1.7A, V_{GS}=0V$ | | | 1.2 | V |
| Diode Continuous Forward Current | I_S | $V_D=V_G, V_S=1.3V$ | | | 1.54 | A |

Note: Surface mounted on 1 in^2 copper pad of FR4 board.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.